

STB-1407SS | Box-motion Servo Side Seal Wrapper

Texwrap quality and reliability

- Servo controlled
- Space-saving
- Easy-to-operate
- Low maintenance
- Saves film

The new 1407SS is Texwrap's latest design advance for applications requiring the moderate speed wrapping of packages where a side seal is desired.

The 1407SS retains all the hallmarks of design and proven reliability that the market has come to expect from Texwrap - all in a brand new compact size. The 2-axis servo head combined with the 140 feet per minute conveyor speed and Texwrap's exclusive Motion Trim™ technology make it the fastest and most flexible wrapper of its kind.

Simplicity and ease-of-use were paramount in the 1407SS design. The controls are easily accessible and intuitive to use. When combined with the color touchscreen controls on the swivel panel, the easy access sliding doors, and the easy-mount-easy-thread film carriage, this machine gives new meaning to the term “operator-friendly”.

The design of the 1407SS will appeal equally to the maintenance department. We eliminated the requirement for shop air by substituting servo drives and we provided easy access to the wrapping area by allowing the sliding operator doors to lift out completely.

From true Generation 3 servo design to solid 24/7 construction, the Texwrap 1407SS provides maximum reliability, ease of use, and minimum maintenance requirements resulting in the lowest total cost of ownership available on the market today.



Made in USA

Distributed by:

Features:

- Laser-cut, heavy steel-frame construction with durable powder-coat finish
- Heavy-duty end seal carriage construction allows higher speeds and virtually eliminates maintenance
- Maximum film/belt speed 140 FPM
- Texwrap's exclusive Versa Seal side seal automatically self-compensates for speed changes
- Variable speed exit conveyor relaxes bridged film at cross seal for stronger seals with less film
- Swivel, color-touchscreen operator panel with diagnostics for machine troubleshooting
- ANSI-compliant interlocked guarding package
- Easy-access sliding doors that lift out, allowing total access for maintenance
- Variable-speed, VFD inverter-duty AC motors
- Powered film delivery system; maximum 24" centerfolded film
- Left-to-right flow is standard
- Center-line wrapper
- Direct lug-to-film transfer available to reduce wrapper length
- Optional centerfolder unit for flat film available
- Optional film splicing kit available

Specifications:

Conveyor Width:	14"W
Cross Seal Width:	18"W
Minimum Pkg Size:	4"L x .5"W
Maximum Pkg Size:	Infinite length x 14"W x 7"H
Film Width:	Maximum 24" centerfolded film
Electrical:	240/208V, 40 amp, 3 phase
Air Requirements:	none
Conveyor Height:	Adjustable from 33" to 38"
Control Panel:	Easy-access swivel-mounted
Footprint:	118"L x 63-7/8"W x 96"H

